

Republic of the Philippines SOCIAL SECURITY SYSTEM NCR OPERATIONS – WEST DIVISION

232 G/F Padilla Delos Reyes Bldg. Juan Luna St. Binondo, Manila Tel. 8395-9897 FAX 243-2464

CANVASS FORM 2022-WEST-AUGUST-01 Tuesday, August 16, 2022

PHILGEPS REF. N	NO.
DATE POSTED:	
POSTED BY:	

Sir / Madam:

Ple	ase furnish us wi	th your qutation on or before:	at 4:00 pm. for t	ne following items:
NO.	QUANTITY	PARTICULARS	UNIT COST	TOTAL COST
	1,168	PURCHASE AND DELIVERY OF LIGHTS	P	P
TECH	NICAL SPECIFIC	ATION:	STATE	MENT OF COMPLIANCE
ple	ase see att.			
	ANTY: One (1) \ D TOTAL APPRO	Year Waranty OVED BUDGET (ABC): P	_	
		Branches (Binondo, Legarda, Manila, Pasay CCP Cainda J. Limcauco of NCR West Division	omplex, Pasay Taft, St	a Mesa, Tondo and Welcome w
	Payment Terms: Delivery Terms: Price Validity:	Supplier shall be paid in acordance to Government 30 Calendar Days upon receipt of approved Purcha Three (3) Months		
2.)	For canvass with Calendar from re Guarantee/Draft The SSS shall w	n an ABC of P 100,000.00 and above the winning bidder eceipt of Notice to Proceed/Job Order/Purchase Order or or 30% Surety Bond callable upon demand of the contra withold the applicable taxes from the amount payable in a	equivalent to 5% Cash, C ct price.	Cashier's/Manager's Check, Bank
4.)	For clarification	of details, please coordinate with Nathalie Alonde at telep	phone no. 8395-9897	
		ising the prescribed/standard canvass form and/or unsea ect SSS Number and TIN-(BIR) of supplier/contractor		e disqualified.
7.)	The bidder shall	offer one (1) quotation only, alternative bids shall be reje	cted.	
8.)	Please send yo including the foll	ur <u>SEALED QUOTATION/CANVASS/BID</u> to 232 Padilowing Eligibility Requirements:	la delos Reyes Bldg., J	uan Luna St., Binondo, Manila <u>.</u>
	a.) Registration proprietorshi	Certificate from SEC (Security Exchange Commissing, or CDA (Cooperative Development Authority) for coop	on), DTI (Department eratives, or any proof of s	of Trade & Industry) for sole such registration.
	c.) BIR 2303	mit issued by the city or municipality where the place of SSS R-5 Contributions Payment egistration	business of the prosper	ctive bidder is
9.)	All payments to supplier prefers	suppliers/creditors/payees shall be done electronically other banks, any charges or fees that will be imposed by	and directly credited to the the bank shall be charge	their Landbank Account. When d to supplier's account.
		Owner/Company Representative (Sign over Printed Name)	<u> </u>	

REMINDER: Price quotation should be made with extra care taking into account the specification and unit of quantity to avoid errors. The offeror binds himself to this quotation **TERMS & CONDITIONS.**

Please indicate below your Business Name, Address and Telephor and Date Received.	ne Number
Your Business Name: Your Business Address:	
Your Business SSS No.:	
Your Business TIN No.: Your Landbank Account No.:	
E-mail Address:	
Telephone Nos.: Fax No.: Date Received:	

Very truly yours,

Nathalie G. Alonde

Canvasser

Len									
Specifications	Item	Description	_	oer		Tot		-	Total Bid Amount
Specifications: Wattage: 15W Luminous Flux: 1,500 Im	1	Specifications: Luminous Efficiency: 120-130 LM/W; Luminous Flux: 2160-2340 Lm Color Temperature: 6500K Daylight; CRI: >80Ra Beam Angle: 150 Degree ; Power: 18W ; Power Supply: Built-in Voltage: 100-277V ; Line Frequency: 50-60Hz Wiring Connection: Single Ended; General Characteristics: Cap Base: G13 ; Lamp Size: 1200mm Length x 26mm Diameter - Material: Aluminum Heat Sink and PC Frosted Cover - Average Lifetime: 50,000 hours(min) '- Standards: CE, RoHS, UL, ETL, TUV, LM79,	₽ 9:	33.00	288	₽	28,224.00		
Ta Tube Light 18W 2FT Industrial Daylight Specifications: Wattage : 18W Liminous Flux : 990 Im Dimension : 600 mm Color Temperature SS00-6500 K / Daylight P		T8 LED Tube Light 16W 4FT Industrial Daylight Specifications: Wattage: 16W Luminous Flux: 1,600 Im Dimension: 1,200 mm Color Temperature 6000-6500 K / Daylight Material: Aluminum Housing + PC Cover PC Cover: Frosted / Clear Light Source: High Brightness LED SMD Beam Angle: 120 Degrees Lifetime: > 50,000 hours Wiring: T8 Connector	₱ 17-	4.00	325	₽	56,550.00		
TS Tube Light 14W 2FT Industrial Daylight Specifications: Wattage : 14W Luminous Flux : 1,400 lm Dimension : 600 mm Color Temperature 5500-6500 K / Daylight Material : Aluminum Housing + PC Cover PC Cover : Frosted / Clear Light Source : High Brightness LED SMD Beam Angle : 120 Degrees Lifetime : > 50,000 hours Wiring : TS Connector Input Voltage : AC 85V - 265V 50/60 Hz Ts Tube Light 28W 4FT Industrial Daylight Specifications: Wattage : 28W Luminous Flux : 2,100 lm Dimension: 1,200 mm Color Temperature 6000-6500 K / Daylight Natienal : Aluminum Housing + PC Cover PC Cover : Frosted / Clear Light Source : High Brightness LED SMD Beam Angle : 120 Degrees Lifetime : > 50,000 hours Wiring : TS Connector Input Voltage : AC 85V - 265V 50/60 Hz Electronic Ballast Specifications: Wattage : 28W Wadde : Lamp 2 x T5 28W P 496.70 So P 24,835.00 P 496.70 Ts T5 28W Ts T5 28W P 496.70 Ts T5 2		T8 Tube Light 18W 2FT Industrial Daylight Specifications: Wattage: 18W Luminous Flux: 990 Im Dimension: 600 mm Color Temperature 5500-6500 K / Daylight Material: Aluminum Housing + PC Cover PC Cover: Frosted / Clear Light Source: High Brightness LED SMD Beam Angle: 120 Degrees Lifetime: > 50,000 hours Wiring: T8 Connector	₱ 6.	3.50	36	₽	2,286.00		
Specifications: Wattage : 28W	4	T5 Tube Light 14W 2FT Industrial Daylight Specifications: Wattage: 14W Luminous Flux: 1,400 lm Dimension: 600 mm Color Temperature 5500-6500 K / Daylight Material: Aluminum Housing + PC Cover PC Cover: Frosted / Clear Light Source: High Brightness LED SMD Beam Angle: 120 Degrees Lifetime: > 50,000 hours Wiring: T5 Connector	₱ 6	1.00	50	₽	3,050.00		
6 Specifications: Wattage : 28W Model : Lamp 2 x 75 28W 7 T8 Tube & Box Type Set (18W) P 496.70 p 24,835.00 p 24,835.00 p 6,750.00		Specifications: Wattage: 28W Luminous Flux: 2,100 lm Dimension: 1,200 mm Color Temperature 6000-6500 K / Daylight Material: Aluminum Housing + PC Cover PC Cover: Frosted / Clear Light Source: High Brightness LED SMD Beam Angle: 120 Degrees Lifetime: > 50,000 hours Wiring: T5 Connector Input Voltage: AC 85V - 265V 50/60 Hz	₽ 7	7.00	394	₽	30,338.00		
	ь	Specifications: Wattage : 28W Model : Lamp 2 x T5 28W					,		
TOTAL 4.00 A 453.000 00	/								